

# ISGUS Terminal IT 4211 IT 4211 FP



## IT 4211 und IT 4211 FP for Access Control

- » User prompting and booking acknowledgement via LED and acoustic signal
- » Door opening via integrated electronic relay or external door control (TSE 400) in the secured area
- » 2 Inputs (closing contact at the terminal)
- » Anti-tampering protection through lid contact
- » Connection to terminal IT 8210 or ACM 40xx possible via network
- » Easy and flexible installation
- » Multi-company feature for up to 10 clients

- » Terminals for Access Control with verification or identification mode (IT 4211 FP)
- » Free choice of up to two fingers per person for fingerprint verification or identification (IT 4211 FP)
- » In combination with ZEUS® Biometrics, ready for integration into any security concept (IT 4211 FP)
- » Fingerprint data capture and transmission to be carried out via the IT 8210 FP terminal (IT 4211 FP)
- » Easy parametrisation via integrated web server

# Technical Data

## IT 4211

## IT 4211 FP



IT 4211



IT 4211 FP

### Badge reading technologies

- » LEGIC advant
- » Mifare Desfire
- » Others upon request

### Power supply

- » 24 V DC
- » PoE acc. IEEE 802.3af

### Typical power consumption

- » 2.03 W (IT 4211)
- » 2.23 W (IT 4211 FP)

### Protection type

- » IP 65 (front side)

### Protection class

- » III / EN 62368-1

### Place of installation

- » Suited for indoor (and outdoor use IT4211)
- » No direct sunlight
- » Ambient temperature: -10° C to + 55° C

### Rel. humidity

- » Max. 85 % (non-condensing)

### Data transmission

- » TCP/IP

### Weight

- » Approx. 0.2 kg (IT 4211)
- » Approx. 0.25 kg (IT 4211 FP)

### Dimensions

IT 4211	IT 4211 FP
» Height: 114 mm	» Height: 155 mm
» Width: 75 mm	» Width: 75 mm
» Depth: 36 mm	» Depth: 60 mm

